

**IN THE CLAIMS:**

Please amend the claims to read as follows:

---

Claims 1-18 (canceled)

19. ~~(Canceled)~~

20. (Currently Amended) The hearing aid according to claim ~~19~~41, wherein said test manager is adapted to disconnect said input transducer from the signal path and to activate said probe means for determination of the signal parameter in order that the noise level generated by C input circuitry of the hearing aid may be determined.

21. ~~(Canceled)~~

22. (Currently Amended) The hearing aid according to claim ~~19~~41, wherein said test manager is adapted to compare the input from said probe with desired parameters in order to establish whether the hearing aid has a defect.

23. (Currently Amended) The hearing aid according to claim ~~21~~24, wherein said second point is selected to achieve that the test signal effects the emission by said output transducer of a sound signal.

24. (Currently Amended) ~~The~~<sup>A</sup> hearing aid comprising, according to claim 21,  
an input transducer for transforming an acoustic input signal into a first electrical signal,  
a signal path including a signal processor for processing the first electrical signal to  
produce a second electrical signal based on the first electrical signal,  
an output transducer for converting the second signal into sound,  
a probe for determining a signal parameter,  
means for connecting said probe to a first point in said signal path,  
a test manager adapted to control a state of the hearing aid, to receive an input from said  
probe and to determine any defect in the hearing aid,

C1 activation means for operator activation in order to cause said test manager to initiate a  
test procedure,

a test signal generator controlled by said test manager and adapted for injecting a test  
signal at a second point in the signal path, and

comprising a filter bank with bandpass filters for deriving from the first electrical signal a  
set of bandpass filtered derivatives of the first electrical signal, wherein said processor is adapted  
to generate the second electrical signal by individual processing of each of the bandpass filtered  
derivatives of the first electrical signal and adding together the processed electrical signals to  
provide the second electrical signal, and wherein said test manager is adapted to selectively  
connect said probe to the output of one of said bandpass filters.

25. (Previously Presented) The hearing aid according to claim 24, wherein said test manager is adapted to connect said probe to the output of a bandpass filter tuned to pick the third harmonic of the output of said test signal generator for determination of harmonic distortion.

26. (Currently Amended) ~~The~~A hearing aid according to ~~claim 23~~ comprising  
a telecoil input transducer for transforming an input signal into a first electrical signal,  
a signal path including a signal processor for processing the first electrical signal to  
produce a second electrical signal based on the first electrical signal,  
an output transducer for converting the second signal into sound,  
a probe for determining a signal parameter,  
means for connecting said probe to a first point in said signal path,  
a test manager adapted to control a state of the hearing aid, to receive an input from said  
probe and to determine any defect in the hearing aid,  
activation means for operator activation in order to cause said test manager to initiate a  
test procedure, and  
a test signal generator controlled by said test manager and adapted for injecting a test  
signal at a second point in the signal path, wherein said second point is selected to achieve that  
the test signal effects the emission by said output transducer of a sound signal,  
and wherein said at least one input/output transducer is a telecoil input transducer, and  
wherein said output transducer is adapted to generate a magnetic field, that is picked up by said  
telecoil input transducer.

27. (Currently Amended) The hearing aid according to claim ~~21~~41, wherein said test manager is adapted to verify the gain of said signal processor.

28. (Currently Amended) The hearing aid according to claim ~~27~~41, wherein said test manager is adapted to verify the gain of said signal processor as a function of frequency.

29. (Currently Amended) The hearing aid according to claim ~~21~~41, wherein said test manager is adapted to verify the compression of said signal processor.

C/ 30. (Currently Amended) The A hearing aid according to ~~claim 19~~, comprising  
an input transducer for transforming an acoustic input signal into a first electrical signal,  
a signal path including a signal processor for processing the first electrical signal to  
produce a second electrical signal based on the first electrical signal,  
an output transducer for converting the second signal into sound,  
a probe for determining a signal parameter,  
means for connecting said probe to a first point in said signal path,  
a test manager adapted to control a state of the hearing aid, to receive an input from said  
probe and to determine any defect in the hearing aid,  
activation means for operator activation in order to cause said test manager to initiate a  
test procedure, and

an adaptive feedback canceller for suppression of acoustic feedback, and wherein said test manager is adapted to verify the operation of said adaptive feedback canceller.

31. (Currently Amended) The hearing aid according to claim ~~19~~41, wherein said activation means comprises a switch positioned at a housing of the hearing aid.

32. (Currently Amended) The hearing aid according to claim ~~19~~41, wherein said activation means comprises an interface adapted to receive commands from a remote control device adapted to operate the hearing aid.

33. (Currently Amended) The hearing aid according to claim ~~19~~41, wherein said activation means comprises an interface adapted to receive commands from a programming device adapted to program the hearing aid.

34. (Currently Amended) The hearing aid according to claim ~~19~~41, wherein said activation means comprises an interface adapted to receive commands from a fitting device for the hearing aid.

35. (Currently Amended) The hearing aid according to claim ~~19~~41, comprising a memory for storage of a reference value of a parameter.

36. (Currently Amended) The hearing aid according to claim ~~19~~41, comprising means for causing generation by said output transducer of a tone signal to alert the user that the hearing aid has a defect.

37. (Previously Presented) The hearing aid according to claim 36, wherein said test manager is adapted to determining a specific type of defect, and comprising means for causing generation by said output transducer of a specific tone signal to alert the user that the hearing aid has a specific defect.

C/ 38. (Currently Amended) The hearing aid according to claim ~~19~~41, comprising at least two switches in said signal path for the selective determination of signal parameters at respective points of said signal path.

39. (Currently Amended) The hearing aid according to claim ~~21~~41, comprising at least two switches in said signal path for the selective injecting of test signals at respective points of said signal path.

40. ~~(Canceled)~~

41. (Currently Amended) A hearing aid comprising  
an input transducer for transforming an acoustic input signal into a first electrical signal,

a filter bank with bandpass filters for deriving from the first electrical signal a set of bandpass filtered derivatives of the first electrical signal,

a signal processor for individual processing of each of the bandpass filtered derivatives of the first electrical signal and adding together the processed electrical signals to provide a second electrical signal based on the first electrical signal,

an output transducer for converting the second signal into sound,

a probe means adapted for being selectively connected to the outputs of each one of said bandpass filters for determining a respective signal parameter,

a test signal generator adapted for injecting a test signal at a selected point in the signal path of the hearing aid extending through said input transducer, said signal processor and said output transducer,

a test manager adapted to control a state of the hearing aid, to receive an input from said probe means and to determine any defect in the hearing aid, and

activation means for operator activation in order to cause said test manager to initiate a test procedure.

42. (Previously Presented) The hearing aid according to claim 23, wherein said test manager is adapted to connect said probe to said input transducer.

43. (New) The hearing aid according to claim 30, comprising a filter bank with bandpass filters for deriving from the first electrical signal a set of bandpass filtered derivatives

of the first electrical signal, wherein said processor is adapted to generate the second electrical signal by individual processing of each of the bandpass filtered derivatives of the first electrical signal and adding together the processed electrical signals to provide the second electrical signal, and wherein said test manager is adapted to selectively connect said probe to the output of one of said bandpass filters.

44. (New) The hearing aid according to claim 30, wherein said test manager is adapted to disconnect said input transducer from the signal path and to activate said probe for determination of the signal parameter in order that the noise level generated by input circuitry of the hearing aid may be determined.

---